

Flowrates

Apex Heritage Cast Iron Gutters

Ref: FR004RW

NOTE: ALL FLOW RATES QUOTED IN LITRES PER SECOND

- Gutter capacities based on BS EN 12056-3:2000, assuming a maximum distance of 50 x gutter depth, from high point to outlet.
- Longer gutters or gutters with corners exceeding 10° will have a reduced capacity.

Gutter Profile	Size (mm)	Pipe/Outlet Diameter (mm)			Pipe/Outlet Size (mm)		
		63	75	100	75x75	100x72	100x100
Half Round	100	1.19	1.22	-	-	-	-
Half Round	113	1.19	1.62	-	-	-	-
Half Round	125	1.19	1.62	2.06	-	-	-
Half Round	152	1.19	1.64	3.14	-	-	-
Beaded Half Round	113	1.19	1.62	-	-	-	-
Beaded Half Round	125	1.19	1.97	2.06	-	-	-
Victorian Ogee	113	1.24	1.8	-	-	-	-
Victorian Ogee	125	1.24	1.97	2.32	-	-	-
Moulded	100x75	1.09	1.64	-	2.24	2.24	-
Moulded	125x100	1.09	1.64	3.21	2.27	3.17	-
Moulded	150x100	1.09	1.64	3.21	2.27	3.17	4.43

For further information contact Alumasc Technical Services

Tel: +44 (0)1744 648400
Email: technical@alumasc-exteriors.co.uk