

Flowrates

GX Pressed Aluminium Gutters

Ref: FR003RW

NOTE: ALL FLOW RATES QUOTED IN LITRES PER SECOND

- Gutter capacities based on BS EN 12056-3:2000, assuming a maximum distance of 50 x gutter depth, from high point to outlet.
- Longer gutters or gutters with corners exceeding 10° will have a reduced capacity.

Gutter Profile	Size (mm)	Pipe/Outlet Diameter (mm)			Pipe/Outlet Size (mm)		
		63	75	100	75x75	100x72	100x100
Joggle	102x76	1.32	1.95	-	2.28	-	-
Joggle	127x102	1.52	2.31	4.14	2.64	3.99	5.23
Joggle	152x102	1.52	2.31	4.14	2.64	3.99	5.23
Joggle	152x152	1.89	2.83	5.16	3.24	4.89	6.59
Joggle	204x152	1.89	2.83	5.16	3.24	4.89	6.59
Smooth	121x75	1.32	1.93	-	2.27	2.87	-
Smooth	140x98	1.52	2.28	3.99	2.61	3.95	5.04
Smooth	170x125	1.73	2.59	4.73	2.97	4.48	6.04
Smooth	176x150	1.9	2.84	5.2	3.26	4.92	6.63
Smooth	224x150	1.88	2.82	5.15	3.23	4.88	6.57
Moulded	113x76	0.99	1.71	-	2.1	-	-
Moulded	139x102	0.99	1.71	3.81	2.1	3.63	5.41
Moulded	162x102	0.99	1.71	3.81	2.1	3.63	5.41
Moulded	175x152	0.99	1.71	3.81	2.1	3.63	5.41
Moulded	207x152	0.99	1.71	3.81	2.1	3.63	5.41

For further information contact Alumasc Technical Services

Tel: +44 (0)1744 648400

Email: technical@alumasc-exteriors.co.uk