

Flowrates

Heritage Cast Aluminium Gutters

Ref: FR001RW

NOTE: ALL FLOW RATES QUOTED IN LITRES PER SECOND

- Gutter capacities based on BS EN 12056-3:2000, assuming a maximum distance of 50 x gutter depth, from high point to outlet.
- Longer gutters or gutters with corners exceeding 10° will have a reduced capacity.

Gutter Profile	Size (mm)	Pipe/Outlet Diameter (mm)			Pipe/Outlet Size (mm)		
		63	75	100	75x75	100x72	100x100
Half Round	100	1.14	1.24	-	1.24	1.24	-
Half Round	113	1.14	1.62	-	1.62	1.62	-
Half Round	125	1.24	2.08	-	2.08	2.08	-
Beaded Half Round	113	1.62	1.62	-	1.62	1.62	-
Beaded Half Round	125	1.77	1.90	-	2.08	2.08	-
Beaded Deep Flow	113	1.77	1.9	-	2.1	3.06	-
Victorian Ogee	110	1.32	1.32	-	1.32	1.32	-
Victorian Ogee	113	1.35	1.82	-	1.82	1.82	-
Victorian Ogee	125	1.35	2.12	-	2.1	2.34	-
Moulded	100x75	1.4	1.64	-	2.1	2.44	-
Moulded	125x100	1.52	1.97	3.81	2.1	4.62	4.62
Moulded	150x100	2.42	2.84	3.81	2.1	4.65	5.12

For further information contact Alumasc Technical Services

Tel: +44 (0)1744 648400
 Email: technical@alumasc-exteriors.co.uk