



- Notes:-
- 1 – Silicone or decorative mineral finish
  - 2 – Glass-fibre scrim reinforcement bedded in ST1
  - 3 – ST1 Composite Mortar
  - 4 – Insulation slab (as per specification)
  - 5 – Breather Membrane (as per architect's specification)
  - 6 – Cement bonded particle board (12mm Pyrok or similar approved)
  - 7 – Insulation between timber studs (dependant upon project requirements)
  - 8 – Timber Framework – Stud (as per architect's specification)
  - 9 – Internal plasterboard with vapour check
  - 10 – Approved mechanical fixing for insulation slabs
  - 11 – Bellcast bead
  - 12 – Skyline coping

**alumasc**  
EXTERIOR BUILDING PRODUCTS

ALUMASC EXTERIOR BUILDING PRODUCTS LTD  
White House Works, Bold Road, Sutton  
St Helens, Merseyside, WA9 4JG, UK  
Telephone: +44 (0)1744 648400  
Facsimile: +44 (0)1744 648401  
Website: www.alumasc-exterior.co.uk  
E-mail: technical@alumasc-exterior.co.uk

Drawing title:  
**Alumasc Skyline Coping System  
Timber Framed Render Wall**

Detail is valid only when approved by the Architect / contractor concerned

Drawing No: SKY-P-03-01  
Scale: NTS  
Drawn by: AEBP

Revision:  
Date: June 2009

Revision:	Rev date:	Drawn by:	Revision:	Description: